


SPIRAALSPANBUS ZWARE UITVOERING - STAAL

Artikelgroep	07.3137
Materiaalsoort	ST
Kwaliteitsklasse	
Draadsoort	
Behandeling	BL
ISO	8748
DIN	7344



d (nom.)*1	1.5	2	2.5	3	4	5	6
d1 min	1.61	2.11	2.62	3.12	4.15	5.15	6.18
d1 max	1.71	2.21	2.73	3.25	4.3	5.35	6.4
d2 max	1.4	1.9	2.4	2.9	3.9	4.85	5.85
a	0.5	0.7	0.7	0.9	1.1	1.3	1.5
s	0.17	0.22	0.28	0.33	0.45	0.56	0.67
*2	1.9	3.5	5.5	7.6	13.5	20	30

*1 = voor de gatmiddellijn wordt d (nom.) met tolerantieveld H12 aanbevolen,

*2 = afschuifkracht tweensnedig min. in kN

Maat	Verpakking	Maat	Verpakking
1.5X4	200	4X18	200
1.5X5	200	4X20	200
1.5X6	200	4X22	200
1.5X8	200	4X24	200
1.5X10	200	4X26	200
1.5X12	200	4X28	200
1.5X14	200	4X30	200
1.5X16	200	4X32	100
2X6	200	4X35	100
2X8	200	4X36	100
2X10	200	4X40	100
2X12	200	5X12	200
2X14	200	5X14	200
2X16	200	5X16	200
2X20	200	5X18	100
2.5X6	200	5X20	100
2.5X8	200	5X22	100
2.5X10	200	5X24	100
2.5X12	200	5X26	100
2.5X14	200	5X28	100
2.5X16	200	5X30	100
2.5X18	200	5X32	100
2.5X20	200	5X35	100
2.5X22	200	5X40	100
2.5X24	200	5X45	100
3X8	200	5X50	100
3X10	200	6X14	100
3X12	200	6X16	100
3X14	200	6X18	100
3X16	200	6X20	100
3X20	200	6X22	100
3X22	200	6X24	100
3X24	200	6X26	100
3X26	200	6X28	100
3X28	200	6X30	100

3X30
3X32
4X10
4X12
4X14
4X16

200	6X32
200	6X35
200	6X40
200	6X50
200	
200	

100
100
100
100