



Shaft diameter range		Nominal dimensions				Designation	
d1		d1	D	b1	b	B1)	
11,91	12,07	12,00	15,50	6,00	8,40	47,60	CR 99049
12,65	12,75	12,70	19,05	6,35	9,93	46,51	CR 99050
13,89	14,00	14,00	19,05	6,35	9,93	46,51	CR 99055
14,22	14,38	14,30	19,05	6,35	9,93	46,51	CR 99056
14,96	15,06	15,00	19,05	5,00	8,99	47,29	CR 99059
15,83	15,93	15,88	19,05	7,95	10,31	50,80	CR 99062
		15,88	19,05	7,95	10,31	50,80	CR 99810 *
15,89	16,00	16,00	18,24	7,95	11,10	50,80	CR 99058
16,94	17,04	17,00	22,23	7,95	11,00	50,80	CR 99068
17,32	17,42	17,37	22,86	7,95	11,13	50,80	CR 99060
17,87	18,00	18,00	24,43	8,00	11,00	46,00	CR 99082
19,00	19,10	19,00	24,00	7,95	11,13	50,80	CR 99811 *
		19,00	24,00	7,95	11,13	50,80	CR 99076
19,27	19,33	19,30	23,83	7,95	11,13	50,80	CR 99081
19,81	19,91	19,86	23,75	7,95	11,13	50,80	CR 99080
19,94	20,04	20,00	23,62	8,00	11,00	50,80	CR 99078
20,62	20,70	20,65	20,65	9,52	14,30	76,20	CR 99083
21,77	21,87	21,82	29,34	6,35	9,52	50,80	CR 99086
21,87	22,00	22,00	30,20	6,58	9,09	47,09	CR 99084
		22,00	30,17	8,00	11,99	46,05	CR 99085
22,18	22,28	22,23	27,79	7,95	11,13	50,80	CR 99812 *
		22,23	27,79	7,95	11,13	50,80	CR 99087
23,06	23,16	23,11	30,94	7,95	11,13	46,91	CR 99091
		23,11	30,94	7,95	11,13	46,91	CR 99860 *
23,87	24,00	24,00	28,70	7,95	11,10	50,80	CR 99092
24,54	24,64	24,59	28,70	15,88	18,26	50,80	CR 99096
		24,59	28,70	7,95	11,13	50,80	CR 99094