



Shaft diameter range

Nominal dimensions

Designation

d1		d1	D	b1	b	B1)	
24,94	25,04	25,00	33,02	7,95	11,00	50,80	CR 99098
		25,00	33,02	7,95	11,00	50,80	CR 99813 *
25,35	25,45	25,40	30,96	7,95	11,13	50,80	CR 99814 *
		25,40	30,96	7,95	11,13	50,80	CR 99100
25,88	26,01	26,00	33,35	8,00	11,99	46,05	CR 99103
26,92	27,02	27,00	33,53	7,95	11,13	46,81	CR 99106
		27,00	33,53	7,95	11,13	46,81	CR 99815 *
27,61	27,71	27,66	35,71	7,95	11,13	15,88	CR 99108
27,94	28,04	28,00	34,92	9,52	12,70	46,81	CR 99111
		28,00	34,92	9,52	12,70	46,81	CR 99866 **
28,53	28,63	28,58	38,10	7,95	11,13	17,48	CR 99816 *
		28,58	38,10	7,95	11,13	17,48	CR 99112
		28,58	38,10	9,52	12,70	17,48	CR 99116
29,31	29,41	29,36	34,29	9,52	12,70	17,48	CR 99120
		29,36	34,29	9,52	12,70	17,48	CR 99865 **
29,80	29,93	29,85	35,56	7,95	11,13	17,48	CR 99122
29,95	30,08	30,00	35,56	8,00	11,00	17,48	CR 99114
30,10	30,23	30,15	35,56	7,95	11,13	17,48	CR 99118
30,88	31,04	31,00	39,70	7,95	11,00	15,88	CR 99123
31,42	31,58	31,50	39,12	8,00	11,10	17,48	CR 99141
31,67	31,83	31,75	38,10	7,95	11,13	17,48	CR 99125
		31,75	38,10	7,95	11,13	17,48	CR 99817 *
31,92	32,08	32,00	38,10	8,00	11,13	17,48	CR 99128
32,94	33,04	33,00	40,49	15,01	18,00	20,65	CR 99121
33,22	33,38	33,30	40,64	6,35	9,50	20,65	CR 99129
33,27	33,43	33,35	40,49	12,70	15,88	20,65	CR 99131
		33,35	40,49	12,70	15,90	20,65	CR 99818 **
33,86	34,01	34,00	41,28	12,70	15,90	20,70	CR 99134