



Shaft diameter range

Nominal dimensions

Designation

d1		d1	D	b1	b	B1)	
49,12	49,28	49,20	56,36	14,30	17,48	25,40	CR 99193
		49,22	56,36	14,30	17,48	25,40	CR 99833 *
49,91	50,07	50,00	57,00	14,00	17,00	24,99	CR 99196
50,21	50,37	50,30	58,75	14,30	17,88	26,67	CR 99198
50,72	50,88	50,80	61,11	14,30	17,48	25,40	CR 99199
		50,80	61,11	22,23	25,40	25,40	CR 99200
		50,80	61,11	14,30	17,48	25,40	CR 99834 *
		50,80	61,11	22,23	25,40	25,40	CR 99835 *
51,81	52,00	52,00	62,71	12,70	15,88	34,52	CR 99204
52,24	52,40	52,32	62,71	19,84	23,83	34,93	CR 99205
53,92	54,06	54,00	61,52	12,70	19,05	32,54	CR 99210
53,95	54,10	54,00	61,52	19,84	23,83	34,92	CR 99836 *
	54,11	54,00	61,52	19,84	23,83	34,93	CR 99212
54,91	55,07	54,99	62,00	19,99	22,99	31,75	CR 99863 *
		55,00	62,00	19,99	22,99	31,75	CR 99215
55,52	55,68	55,60	63,50	19,84	23,83	33,35	CR 99218
55,81	56,00	56,00	64,29	19,79	23,77	80,01	CR 99224
		56,00	64,29	12,70	15,88	33,35	CR 99220
56,56	56,72	56,64	64,29	12,70	15,88	33,35	CR 99229
		56,64	64,29	19,84	23,01	31,75	CR 99230
56,57	56,72	56,64	64,29	12,70	15,88	33,35	CR 99861 **
56,82	56,98	56,90	65,10	19,41	22,86	31,75	CR 99226
57,12	57,28	57,15	64,29	19,84	23,83	33,35	CR 99837 *
		57,20	64,29	7,95	11,13	33,35	CR 99227
		57,20	64,29	19,84	23,83	33,35	CR 99225
57,13	57,28	57,15	64,29	7,95	11,13	33,35	CR 99838 **
57,91	58,06	58,00	65,99	19,84	23,83	34,92	CR 99219
58,64	58,80	58,72	68,28	19,84	23,83	34,93	CR 99231
59,10	59,26	59,18	69,85	19,05	22,23	38,10	CR 99233