



order number	dH7 (mm)	Dh5 (mm)	L (mm)	b (mm)	t (mm)	b1 (mm)	t1 (mm)	weight (kg)	nmax (tr/min)	load capacity 1	load capacity 2	type of bearing	TN (N.m)	no load torque (N.m)
UK 8 ZZ 8-0.01	22		9	-	-	-	-	0.02	15000	3300	860	-	2.5	0.005
UK 12 ZZ	12-0.01	32	10	-	-	-	-	0.04	10000	6100	2770	6201 ZZ	9.3	0.007
UK 15 ZZ	15-0.01	35	11	-	-	-	-	0.06	8400	7400	3400	6202 ZZ	16.9	0.009
UK 17 ZZ	17-0.01	40	12	-	-	-	-	0.07	7350	7900	3800	6203 ZZ	30.6	0.011
UK 20 ZZ	20-0.01	47	14	-	-	-	-	0.11	6000	9400	4450	6204 ZZ	50	0.013
UK 25 ZZ	25-0.01	52	15	-	-	-	-	0.14	5200	10700	5450	6205 ZZ	85	0.02
UK 30 ZZ	30-0.01	62	16	-	-	-	-	0.21	4200	11700	6450	6206 ZZ	138	0.044
UK 35 ZZ	35-0.01	72	17	-	-	-	-	0.3	3600	12600	7250	6207 ZZ	175	0.058
UK 40 ZZ	40-0.01	80	22	-	-	-	-	0.5	3000	15540	12250	-	325	0.07
UKC 12 ZZ	12H7	32	10	4	1.3	-	-	0.04	10000	6100	2770	6201 ZZ	9.3	0.007
UKC 15 ZZ	15H7	35	11	5	1.2	-	-	0.06	8400	7400	3400	6202 ZZ	16.9	0.009
UKC 17 ZZ	17H7	40	12	5	1.2	-	-	0.07	7350	7900	3800	6203 ZZ	30.6	0.011
UKC 20 ZZ	20H7	47	14	6	1.6	-	-	0.11	6000	9400	4450	6204 ZZ	50	0.013
UKC 25 ZZ	25H7	52	15	8	2	-	-	0.14	5200	10700	5450	6205 ZZ	85	0.02
UKC 30 ZZ	30H7	62	16	8	2	-	-	0.21	4200	11700	6450	6206 ZZ	138	0.044
UKC 35 ZZ	35H7	72	17	10	2.4	-	-	0.3	3600	12600	7250	6207 ZZ	175	0.058
UKC 40 ZZ	40H7	80	22	12	3.3	-	-	0.5	3000	15540	12250	-	325	0.07
UKCC 17 ZZ	17H7	40	12	5	1.2	2	1	0.07	7350	7900	3800	6203 ZZ	30.6	0.011
UKCC 20 ZZ	20H7	47	14	6	1.6	3	1.5	0.11	6000	9400	4450	6204 ZZ	50	0.013
UKCC 25 ZZ	25H7	52	15	8	2	6	2	0.14	5200	10700	5450	6205 ZZ	85	0.02
UKCC 30 ZZ	30H7	62	16	8	2	6	2	0.21	4200	11700	6450	6206 ZZ	138	0.044
UKCC 35 ZZ	35H7	72	17	10	2.4	8	2.5	0.3	3600	12600	7250	6207 ZZ	175	0.058
UKCC 40 ZZ	40H7	80	22	12	3.3	10	3	0.5	3000	15540	12250	-	325	0.07
UK 20 2RS	20-0.01	47	19	-	-	-	-	0.15	6000	9400	4450	-	50	0.06
UK 25 2RS	25-0.01	52	20	-	-	-	-	0.18	5200	10700	5450	-	85	0.06
UK 30 2RS	30-0.01	62	21	-	-	-	-	0.27	4200	11700	6450	-	138	0.075