



Axial angular contact ball bearings

234426-M-SP (Series 2344)

double direction, separable, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	130 mm
D	200 mm
B	84 mm
B ₁	21 mm
C	42 mm
d ₁	177 mm
D _a	188 mm Tolerance: H12
d _a	159 mm Tolerance: h12
d _s	6,3 mm
n _s	12,2 mm
r ₁	0,6 mm
r ₁ min	
r _{a1}	0,6 mm
r _{a1} max	
r _a	2 mm
r _a max	
r _{min}	2 mm
α	60 ° Contact angle
m	6,86 kg Mass
C _a	128000 N Basic dynamic load rating, axial
C _{0a}	440000 N Basic static load rating, axial
n _G Fett	2800 1/min Limiting speed for grease lubrication
n _G Öl	3800 1/min Limiting speed for minimal quantity oil lubrication
C _{ua}	30500 N Fatigue limit load, axial

