



Axial angular contact ball bearings

234432-M-SP (Series 2344)

double direction, separable, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	160 mm
D	240 mm
B	96 mm
B ₁	24 mm
C	48 mm
d ₁	212 mm
D _a	226 mm Tolerance: H12
d _a	192,5 mm Tolerance: h12
d _s	8 mm
n _s	15 mm
r ₁	0,6 mm
min	
r _{a1}	0,6 mm
max	
r _a	2,1 mm
max	
r _{min}	2,1 mm
α	60 ° Contact angle
m	11,1 kg Mass
C _a	168000 N Basic dynamic load rating, axial
C _{0a}	600000 N Basic static load rating, axial
n _G	2400 1/min Limiting speed for grease lubrication
Fett	
n _G	3400 1/min Limiting speed for minimal quantity oil lubrication
Öl	
C _{ua}	38000 N Fatigue limit load, axial

