

Axial angular contact ball bearings

7602035-TVP (Series 7602)

single direction, with contact angle $\alpha = 60^\circ$, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	35 mm	Tolerance: 0/-0,006
D	72 mm	Tolerance: 0/-0,007
B	17 mm	Tolerance: 0/-0,12
	60 °	Contact angle
a	55 mm	
Da	60,5 mm	Tolerance: H12
da	46,5 mm	Tolerance: h12
r1	1,1 mm	
rmin	1,1 mm	
m	0,339 kg	Mass
Ca	31500 N	Basic dynamic load rating, axial
C0a	81000 N	Basic static load rating, axial
Cua	3600 N	Fatigue limit load, axial
nG	5700 1/min	Limiting speed for grease lubrication
Fett		
n9	3200 1/min	
MRL	0,115 Nm	Bearing frictional torque Valid for individual bearing with stated preload force, bearing lightly oiled.
CaL	1020 N/μm	Axial rigidity Valid for matched pair of bearings in O or X arrangement
	2 μm	Axial runout The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM35	Designation of recommended INA locknut

MA	AM35	Designation of recommended INA locknut
	40 Nm	Tightening torque
	Only valid in conjunction with INA precision locknuts	
	11310 N	Axial preload force



