



Rod ends GIKL18-PB (Series GIKL..-PB)

with internal thread, requiring maintenance, to DIN ISO 12240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	18 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,018 / 0
d2	46 mm	
l4	94 mm	
	0 - 0,035 mm	Radial internal clearance Deviation from DIN 12240-1, dimension series K
B	23 mm	Tolerance: 0 / -0,12
C ₁	16,5 mm	
D	35 mm	
d ₁	21,8 mm	
d ₃	M18X1,5	
d ₄	25 mm	
d ₅	31 mm	
dk	31,75 mm	
h ₁	71 mm	
l ₃	32 mm	
l ₅	10 mm	
l ₇	25 mm	
r _{1s} min	0,3 mm	Chamfer dimension
W	27 mm	
α	15 °	
m	0,32 kg	Mass
C _r	26200 N	Basic dynamic load rating, radial

Cor	47000 N Basic static load rating, radial Basic load rating of housing
-----	--

