


**FAG****HCB71913-E-2RSD-T-P4S-UL** [🔗](#)

Spindle bearing

Schaeffler ID:
0387916170000Spindle bearings HCB719..-E-2RSD, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, with ceramic balls, lip seals on both sides, non-contact, restricted tolerances

Technical information



Main Dimensions & Performance Data


d	65 mm	Bore diameter
D	90 mm	Outside diameter
B	13 mm	Width
C_r	23.800 N	Basic dynamic load rating, radial
C_{0r}	15.300 N	Basic static load rating, radial
C_{ur}	1.230 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	19.000 1/min	Limiting speed for grease lubrication
$\approx m$	170,59 g	Weight

Mounting dimensions

d_a	70 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	85,5 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \text{ max}}$	0,6 mm	Maximum recess radius
$r_{a1 \text{ max}}$	0,3 mm	Maximum recess radius
a	24,6 mm	Distance between the apexes of the pressure cones

Dimensions

r_{min}	1 mm	Minimum chamfer dimension
$r_{1 \text{ min}}$	1 mm	Minimum chamfer dimension
α	25 °	Contact angle






View product details on medias

07.10.2024, 08:48:37 CEST

SCHAEFFLER



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Additional information

F _{VL}	58 N	Preload force light
F _{VM}	309 N	Preload force medium
F _{VH}	723 N	Preload force heavy
K _{aEL}	165 N	Lift-off force light
K _{aEM}	904 N	Lift-off force medium
K _{aEH}	2.165 N	Lift-off force heavy
C _{aL}	102 N/μm	Axial rigidity light
C _{aM}	185 N/μm	Axial rigidity medium
C _{aH}	255 N/μm	Axial rigidity heavy