

/medias/en!hp.ec.br.pr//medias/en!hp.pv/81.83.3.25NN30...-K-TVP-SPHochgenauigkeits-Zylinderroll

Super precision cylindrical roller bearings NN3006-D-K-TVP-SP-XL (Series NN30...-K-TVP-SP)



Non-locating bearing, double row, with tapered bore, taper
1:12, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm
D	55 mm
B	19 mm
Da max	50 mm Tolerance: H12
da min	38,5 mm Tolerance: h12
E	48,5 mm
r1 min	1 mm
ra1 max	1 mm
s	1,7 mm Axial displacement facility from central position
m	0,18 kg ≈ Mass
Cr	30000 N Basic dynamic load rating, radial
Cor	31000 N Basic static load rating, radial
Cur	4450 N Fatigue limit load, radial
ng Fett	20600 1/min Limiting speed for grease lubrication
ng Öl	24200 1/min Limiting speed for minimal quantity oil lubrication



