

Cylindrical roller bearings

NN3012-AS-K-M-SP (Series NN30..-AS-K-M-SP)

main dimensions to DIN 5412-4, non-locating bearing,
double row, with tapered bore, taper 1:12, separable, with
cage, reduced radial internal clearance, restricted
tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	60 mm
D	95 mm
B	26 mm
d ₁	73,3 mm
D _a max	88 mm Tolerance: H12
d _a min	70,1 mm Tolerance: h12
D _b min	88 mm
d _s	3,2 mm
E	86,1 mm
n _s	4,8 mm
r _a max	1 mm
r _{min}	1,1 mm
s	1,9 mm Axial displacement facility from central position
m	0,674 kg Mass
C _r	76000 N Basic dynamic load rating, radial
C _{0r}	111000 N Basic static load rating, radial

n _G	9100 1/min	Limiting speed for grease lubrication
Fett		
n _G	10700 1/min	Limiting speed for minimal quantity oil lubrication
Öl		
C _{ur}	14500 N	Fatigue limit load, radial
C _{rL}	1410	spring stiffness, radial



