



# Linear roller bearings RUS26086 (Series RUS)

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

A	40 mm
C <sub>8</sub>	92 mm
H	26 mm
A <sub>2</sub>	30 mm Tolerance: +/-0,1
C	86 mm
C <sub>1</sub>	53 mm
C <sub>2</sub>	28 mm Tolerance: +/-0,1
C <sub>9</sub>	63 mm Minimum support length
H <sub>1</sub>	0,2 mm
h <sub>4</sub>	21 mm
K <sub>2</sub>	M6 According to DIN 912-12.9 The values apply to screws with a preservative. If there is a possibility of settling, the screws should be secured against rotation. It must be ensured that the adjacent construction has adequate strength. See VDI Guideline 2230.
K <sub>3</sub>	M4 According to DIN 912-12.9 The values apply to screws with a preservative. If there is a possibility of settling, the screws should be secured against rotation. It must be ensured that the adjacent construction has adequate strength. See VDI Guideline 2230.
L <sub>w</sub>	14 mm
t	10 mm
m	0,41 kg Mass
C	76000 N
C <sub>0</sub>	56000 N

