

/medias/en!hp.ec.br.pr//medias/en!hp.pv/81.83.3.25ukfcUKFCGehäuseeinheiten

# Housing units UKFC212 (Series UKFC)

four-bolt flanged housing units, round design, cast iron, adapter sleeve, RSR seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

|                       |                                               |
|-----------------------|-----------------------------------------------|
| d                     | 55 mm                                         |
| H                     | 195 mm                                        |
| B <sub>1</sub>        | 62 mm                                         |
| A                     | 36 mm                                         |
| A <sub>1</sub>        | 15 mm                                         |
| A <sub>2</sub>        | 17 mm                                         |
| d <sub>3</sub><br>max | 80 mm                                         |
| J                     | 160 mm                                        |
| N                     | 19 mm                                         |
| N <sub>1</sub>        | 113,1 mm                                      |
| T <sub>1</sub>        | 12 mm                                         |
| U                     | 51,2 mm                                       |
| Z                     | 135 mm Tolerance: h8                          |
| m                     | 4,95 kg Mass                                  |
|                       | FC212 Designation, housing                    |
|                       | UK212 Designation, radial insert ball bearing |

