

Spindle bearings B71902-C-T-P4S

(Series B719..-C)

adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	15 mm
D	28 mm
B	7 mm
a	6 mm
Da	25,5 mm Tolerance: H12
da	18 mm Tolerance: h12
E _{tk} nom	20,9 mm
r ₁ min	0,3 mm
r _{a1} max	0,3 mm
r _a max	0,3 mm
r _{min}	0,3 mm
α	15 ° Contact angle
m	0,016 kg Mass
C _r	5100 N Basic dynamic load rating, radial
C _{0r}	2030 N Basic static load rating, radial
n _G Fett	56000 1/min Limiting speed for grease lubrication
n _G Öl	85000 1/min Limiting speed for minimal quantity oil lubrication
C _{ur}	209 N Fatigue limit load, radial
F _v	19 N Preload force

L	
Fv	73 N Preload force
M	
Fv	153 N Preload force
H	
KaE	59 N Lift-off force
L	
KaE	249 N Lift-off force
M	
KaE	559 N Lift-off force
H	
Ca	16,4 N Axial rigidity
L	
Ca	30,5 N Axial rigidity
M	
Ca	44,9 N Axial rigidity
H	



