

Spindle bearings B71905-C-T-P4S

(Series B719..-C)

adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm
D	42 mm
B	9 mm
a	9 mm
Da	38,5 mm Tolerance: H12
da	29 mm Tolerance: h12
E _{tk} nom	31,8 mm
r ₁ min	0,3 mm
r _{a1} max	0,3 mm
r _a max	0,3 mm
r _{min}	0,3 mm
α	15 ° Contact angle
m	0,043 kg Mass
C _r	8300 N Basic dynamic load rating, radial
C _{0r}	4050 N Basic static load rating, radial
n _G Fett	36000 1/min Limiting speed for grease lubrication
n _G Öl	56000 1/min Limiting speed for minimal quantity oil lubrication
C _{ur}	415 N Fatigue limit load, radial
F _v	33 N Preload force

L	
Fv	124 N Preload force
M	
Fv	258 N Preload force
H	
KaE	102 N Lift-off force
L	
KaE	418 N Lift-off force
M	
KaE	934 N Lift-off force
H	
Ca	24,9 N Axial rigidity
L	
Ca	45,4 N Axial rigidity
M	
Ca	66,3 N Axial rigidity
H	



