

Spindle bearings B7216-C-T-P4S

(Series B72..-C)

adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	80 mm
D	140 mm
B	26 mm
a	28 mm
Da	129 mm Tolerance: H12
da	91 mm Tolerance: h12
E _{tk} nom	104,3 mm
r ₁ min	2 mm
r _{a1} max	2 mm
r _a max	2 mm
r _{min}	2 mm
α	15 ° Contact angle
m	1,43 kg Mass
C _r	94000 N Basic dynamic load rating, radial
C _{0r}	55000 N Basic static load rating, radial
n _G Fett	10000 1/min Limiting speed for grease lubrication
n _G Öl	17000 1/min Limiting speed for minimal quantity oil lubrication
C _{ur}	5400 N Fatigue limit load, radial
F _v	549 N Preload force

L	
Fv	1721 N Preload force
M	
Fv	3412 N Preload force
H	
KaE	1701 N Lift-off force
L	
KaE	5781 N Lift-off force
M	
KaE	12250 N Lift-off force
H	
Ca	94,1 N Axial rigidity
L	
Ca	158,8 N Axial rigidity
M	
Ca	225,9 N Axial rigidity
H	



