

Spindle bearings B7218-C-T-P4S

(Series B72..-C)

adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	90 mm
D	160 mm
B	30 mm
a	32 mm
Da	147 mm Tolerance: H12
da	104 mm Tolerance: h12
E _{tk} nom	118,8 mm
r ₁ min	2 mm
r _{a1} max	2 mm
r _a max	2 mm
r _{min}	2 mm
α	15 ° Contact angle
m	2,2 kg Mass
C _r	125000 N Basic dynamic load rating, radial
C _{0r}	75000 N Basic static load rating, radial
n _G Fett	8500 1/min Limiting speed for grease lubrication
n _G Öl	14000 1/min Limiting speed for minimal quantity oil lubrication
C _{ur}	6900 N Fatigue limit load, radial
F _v	732 N Preload force

L	
Fv	2280 N Preload force
M	
Fv	4513 N Preload force
H	
KaE	2267 N Lift-off force
L	
KaE	7640 N Lift-off force
M	
KaE	16156 N Lift-off force
H	
Ca	108,9 N Axial rigidity
L	
Ca	182,8 N Axial rigidity
M	
Ca	259,5 N Axial rigidity
H	



