

Spindle bearings B7219-C-T-P4S

(Series B72..-C)

adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	95 mm
D	170 mm
B	32 mm
a	34 mm
Da	154 mm Tolerance: H12
da	110,5 mm Tolerance: h12
E _{tk} nom	125,8 mm
r ₁ min	2,1 mm
r _{a1} max	2 mm
r _a max	2 mm
r _{min}	2,1 mm
α	15 ° Contact angle
m	2,73 kg Mass
C _r	130000 N Basic dynamic load rating, radial
C _{0r}	81000 N Basic static load rating, radial
n _G Fett	8000 1/min Limiting speed for grease lubrication
n _G Öl	13000 1/min Limiting speed for minimal quantity oil lubrication
C _{ur}	7300 N Fatigue limit load, radial
F _v	760 N Preload force

L	
Fv	2373 N Preload force
M	
Fv	4703 N Preload force
H	
KaE	2353 N Lift-off force
L	
KaE	7935 N Lift-off force
M	
KaE	16792 N Lift-off force
H	
Ca	114,9 N Axial rigidity
L	
Ca	192,7 N Axial rigidity
M	
Ca	273,4 N Axial rigidity
H	



