



Rod ends GIKSR30-PS (Series GIKSR..-PS)

with internal thread, made from special steel,
maintenance-free, to DIN ISO 12 240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,021 / 0
d2	71 mm	
max		
l4	145,5 mm	
	0,010 - 0,055 mm	Radial internal clearance
B	37 mm	Tolerance: 0 / -0,12
C1	25 mm	
D	55 mm	
d1	34,8 mm	
d3	M30X2	
d4	40 mm	
d5	50 mm	
dk	50,8 mm	
h1	110 mm	
l3	45 mm	
min		
l5	15 mm	
l7	35 mm	
min		
r1s	0,3 mm	Chamfer dimension
min		
W	41 mm	
α	15 °	
m	1,15 kg	Mass

C_r	114000 N	Basic dynamic load rating, radial
C_{or}	47500 N	Basic static load rating, radial
		Basic load rating of housing

