



Rod ends GIKSR5-PS (Series GIKSR..-PS)

with internal thread, made from special steel,
maintenance-free, to DIN ISO 12 240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	5 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,012 / 0
d2	19 mm	
max		
l4	36,5 mm	
	0,003 - 0,035 mm	Radial internal clearance
B	8 mm	Tolerance: 0 / -0,12
C1	6 mm	
D	13 mm	
d1	7,7 mm	
d3	M5	
d4	9 mm	
d5	11 mm	
dk	11,1 mm	
h1	27 mm	
l3	8 mm	
min		
l5	4 mm	
l7	9 mm	
min		
r1s	0,3 mm	Chamfer dimension
min		
W	9 mm	
α	13 °	
m	0,017 kg	Mass

C_r	6000 N Basic dynamic load rating, radial
C_{or}	3800 N Basic static load rating, radial
	Basic load rating of housing

