

Plummer block housing units PASE50-N-FA125 (Series PASE..-FA125)

cast iron housing, radial insert ball bearing with eccentric locking collar, P seals, with anti-corrosion protection

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	50	mm	
L	200	mm	
H_2	115	mm	
A	54	mm	
A_1	34	mm	
B_1	43,8	mm	
d_3 max	69	mm	
H	57,2	mm	
H_1	21,5	mm	
J	158	mm	
N	18	mm	
N_1	23	mm	
Q	Rp1/8		
S_1	32,8	mm	
m	2,47	kg	Mass
C_r	37500	N	Basic dynamic load rating, radial
C_{0r}	23200	N	Basic static load rating, radial
	GG.ASE10-N-FA125.1		Designation of housing
	GRAE50-NPP-B-FA125.5		Designation of bearing
	KASK10		Bearing end cap, closed design. To be ordered separately.

Slot for bearing end cap



