



# Housing units RCJ45 (Series RCJ)

four-bolt flanged housing units, cast iron, eccentric locking collar, R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

|                 |   |
|-----------------|---|
| d               | 45 mm                                     |
| L               | 137 mm                                    |
| U               | 59,1 mm                                   |
| A               | 35 mm                                     |
| A <sub>1</sub>  | 13 mm                                     |
| A <sub>2</sub>  | 24 mm                                     |
| B <sub>1</sub>  | 56,5 mm                                   |
| d <sub>3</sub>  | 63 mm                                     |
| max             |   |
| J               | 105 mm                                    |
| N               | 14 mm                                     |
| Q               | Rp1/8                                     |
| V               | 116 mm                                    |
| m               | 2,26 kg Mass                              |
| C <sub>r</sub>  | 34500 N Basic dynamic load rating, radial |
| C <sub>0r</sub> | 20400 N Basic static load rating, radial  |
|                 | GG.CJ09 Designation of housing            |
|                 | GE45-KRR-B Designation of bearing         |

