



# Housing units RCSMF30 (Series RCSMF)



two-bolt flanged housing units, sheet steel, rubber interliner, eccentric locking collar, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm
H	114 mm
U	35 mm
A	27 mm
A <sub>2</sub>	15 mm
B <sub>1</sub>	26,5 mm
d <sub>3</sub>	42,5 mm
max	
J	92 mm
L	70 mm
N	10,5 mm
S	1,5 mm
V	68 mm
m	0,32 kg Mass
C <sub>g</sub>	1400 N Load carrying capacity of housing, radial
C <sub>r</sub>	14100 N Basic dynamic load rating, radial
C <sub>0r</sub>	8300 N Basic static load rating, radial
FLAN65-RCSMF-FA125	Designation of housing Housing with Corrotect® coating.
RALE30-NPP-FA106	Designation of bearing
GRG.RCSM55/65	Designation of rubber interliner

