



# Plummer block housing units

## RSAO40 (Series RSAO)

cast iron housing, radial insert ball bearing with eccentric locking collar, R seals



The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

|                 |   |
|-----------------|---|
| d               | 40 mm                                     |
| L               | 220 mm                                    |
| H <sub>2</sub>  | 116 mm                                    |
| A               | 60 mm                                     |
| A <sub>1</sub>  | 31 mm                                     |
| B <sub>1</sub>  | 54,6 mm                                   |
| d <sub>3</sub>  | 63 mm                                     |
| max             |   |
| H               | 60 mm                                     |
| H <sub>1</sub>  | 22 mm                                     |
| J               | 170 mm                                    |
| N               | 17,5 mm                                   |
| N <sub>1</sub>  | 27,5 mm                                   |
| Q               | Rp1/8                                     |
| S <sub>1</sub>  | 36,6 mm                                   |
| m               | 3,18 kg Mass                              |
| C <sub>r</sub>  | 47000 N Basic dynamic load rating, radial |
| C <sub>0r</sub> | 26000 N Basic static load rating, radial  |
|                 | GG.SAO08 Designation of housing           |
|                 | GNE40-KRR-B Designation of bearing        |

