

KETTINGWIELEN - TRIPLEX

Voor rollenketting 08B-3

Vlgs. Din 8187

1/2" x 5/16"

Tanden aantal	Boring		Naaf afmeting		Steek cirkel	Kop cirkel	Gewicht
Z	D1 mm	max. mm	Dm mm	A mm	Dp mm	De mm	ca. kg
8	10	13	20	46	33,18	38,00	0,13
9	12	15	24	46	37,13	42,00	0,18
10	12	18	28	46	41,10	45,90	0,24
11	16	21	32	50	45,07	49,90	0,31
12	16	23	35	50	49,07	53,90	0,39
13	16	25	38	50	53,06	57,90	0,49
14	16	27	42	50	57,07	61,90	0,60
15	16	31	46	50	61,09	65,90	0,72
16	16	33	50	50	65,10	69,90	0,85
17	16	35	54	50	69,11	74,00	0,99
18	16	38	58	50	73,14	78,00	1,14
19	16	41	62	50	77,16	82,00	1,30
20	16	44	66	50	81,19	86,00	1,47
21	16	47	70	55	85,22	90,10	1,79
22	16	47	70	55	89,24	94,10	1,93
23	16	47	70	55	93,27	98,10	2,08
24	16	50	75	55	97,29	102,10	2,32
25	16	53	80	55	101,33	106,20	2,57
26	20	56	85	55	105,36	110,20	2,79
27	20	56	85	55	109,40	114,20	2,96
28	20	60	90	55	113,42	118,30	3,25
29	20	63	95	55	117,46	122,30	3,55
30	20	66	100	55	121,50	126,30	3,86
31	20	73	110	55	125,54	130,40	4,32
32	20	73	110	55	129,56	134,40	4,53
33	20	73	110	55	133,60	138,40	4,74
34	20	73	110	55	137,64	142,50	4,97
35	20	73	110	55	141,68	146,50	5,20
36	25	80	120	55	145,72	150,60	5,64
37	25	80	120	55	149,76	154,60	5,88
38	25	80	120	55	153,80	158,60	6,14
39	25	80	120	55	157,83	162,70	6,40
40	25	80	120	55	161,87	166,70	6,66
42	25	80	120	60	169,95	176,50	7,54
45	25	80	120	60	182,07	188,60	9,12
46	25	80	120	60	186,10	192,60	9,51
48	25	80	120	60	194,18	200,70	9,33
50	25	80	120	60	202,26	208,80	10,74
52	25	80	120	60	210,34	216,90	11,23
55	25	80	120	60	222,46	229,00	12,51
57	25	80	120	60	230,54	237,10	13,26
60	25	80	120	60	242,66	249,20	14,47
76	25	80	120	60	307,33	313,90	21,78
95	25	80	120	60	384,11	390,70	34,00
114	30	90	135	70	460,90	467,40	39,50

Ook afwijkende tandenaantallen op voorraad, specificaties op aanvraag.

Steek	P	= 12,70 mm
Binnenbreedte	E	= 7,750 mm
Roldiameter	D3	= 8,510 mm
Tandbreedte	b1	= 7,000 mm
	B3	= 34,90 mm

materiaal: staal C45

