


KETTINGWIELEN - TRIPLEX

Voor rollenketting 10B-3

Vlgs. Din 8187

5/8" x 3/8"

Tanden aantal	Boring		Naaf afmeting		Steek cirkel	Kop cirkel	Gewicht
Z	D1 mm	max. mm	Dm mm	A mm	Dp mm	De mm	ca. kg
8	12	16	25	55	41,48	48,40	0,27
9	12	19	30	55	46,42	53,30	0,38
10	16	23	35	55	51,37	58,30	0,47
11	16	26	39	55	56,35	63,20	0,61
12	16	29	44	55	61,34	68,20	0,78
13	16	32	49	55	66,33	73,20	0,96
14	16	35	54	55	71,34	78,20	1,15
15	16	39	59	55	76,36	83,20	1,37
16	16	43	64	60	81,37	88,30	1,72
17	16	46	69	60	86,39	93,30	1,99
18	16	49	74	60	91,42	98,30	2,27
19	16	52	79	60	96,45	103,30	2,58
20	16	55	84	60	101,48	108,40	2,91
21	20	56	85	60	106,51	113,40	3,12
22	20	60	90	60	111,55	118,40	3,48
23	20	63	95	60	116,58	123,50	3,86
24	20	66	100	60	121,62	128,50	4,25
25	20	70	105	60	126,66	133,60	4,67
26	20	73	110	60	131,70	138,60	5,10
27	20	73	110	60	136,74	143,60	5,43
28	20	76	115	60	141,78	148,70	5,90
29	20	76	115	60	146,83	153,70	6,25
30	20	80	120	60	151,87	158,80	6,65
31	20	80	120	60	156,92	163,80	7,18
32	20	80	120	60	161,96	168,90	7,56
33	20	80	120	60	167,01	173,90	7,97
34	20	80	120	60	172,05	178,90	8,36
35	20	80	120	60	177,10	184,00	8,74
36	25	80	120	60	182,15	189,00	9,15
37	25	80	120	60	187,19	194,10	9,61
38	25	80	120	60	192,24	199,10	10,08
39	25	80	120	60	197,29	204,20	10,57
40	25	80	120	60	202,34	209,20	11,07
42	25	85	130	60	212,43	220,80	12,66
45	25	85	130	60	227,58	236,00	15,70
46	25	85	130	60	232,63	241,00	16,15
48	25	85	130	60	242,73	251,10	17,24
50	25	85	130	60	252,82	261,20	18,83
55	25	85	130	60	278,08	286,50	22,01
57	25	85	130	60	288,18	296,60	23,40
60	25	85	130	67	303,33	311,70	25,80
76	25	85	130	67	384,15	392,50	40,25
95	30	85	130	76	480,14	488,50	55,35
114	30	85	130	67	576,13	584,50	



Ook afwijkende tandenaantallen op voorraad, specificaties op aanvraag.

Steek	P	=	15,875 mm
Binnenbreedte	E	=	9,650 mm
Roldiameter	D3	=	10,16 mm
Tandbreedte	b1	=	9,000 mm
	B3	=	42,10 mm

materiaal: staal C45