

## 2721MF

Lamps for printed circuit boards



### Areas of application

- Instrument and switch lighting

### Product benefits

- OEM Quality
- Wide product range
- Reliable quality

### Product features

- Original spare parts

Technical data


Electrical data

Power input	1.2 W
Nominal wattage	1.2 W
Nominal voltage	12 V
Power input tolerance	±10 %
Test voltage	13.5 V

Light technical data

Luminous flux	6.4 lm
Luminous flux tolerance	±25 %

Dimensions & weight



Product line drawing

Length	40.0 mm
Diameter	5.0 mm
Product weight	1.17 g

Colors & materials

Base color	Jet black
------------	-----------

Lifespan

Lifespan B3	500 h
Lifespan Tc	2000 h

Additional product data

Product datasheet

Base (standard designation)	B8.5d
-----------------------------	-------

Capabilities

Thickness of PCB	1.6 mm
------------------	--------

Certificates & standards

ECE category	-
--------------	---

Country specific categorizations

Order reference	2721MF
-----------------	--------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300891255	OSRA2721MF	-	-	-

## Product datasheet

---

### Logistical Data

---

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321349545	2721MF	Blister 2	46 mm x 13 mm x 52 mm	0.03 dm <sup>3</sup>	17.00 g
4008321349552	2721MF	Shipping carton box 20	80 mm x 112 mm x 137 mm	1.23 dm <sup>3</sup>	116.00 g
4050300891255	2721MF	Unpacked 1	13 mm x 10 mm x 15 mm	0.00 dm <sup>3</sup>	1.33 g
4008321043085	2721MF	Folding carton box 10	114 mm x 46 mm x 27 mm	0.14 dm <sup>3</sup>	12.40 g
4008321096753	2721MF	Shipping carton box 50	115 mm x 55 mm x 148 mm	0.94 dm <sup>3</sup>	127.60 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

---

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.