


7307 BECBP


SKF Explorer

Dimensions



d		35	mm
D		80	mm
B		21	mm
d ₁	≈	52.65	mm
d ₂	≈	43.62	mm
D ₁	≈	63.45	mm
a		35	mm
r _{1,2}	min.	1.5	mm
r _{3,4}	min.	1	mm

Abutment dimensions



d _a	min.	44	mm
D _a	max.	71	mm
D _b	max.	74.4	mm
r _a	max.	1.5	mm
r _b	max.	1	mm

Calculation data

Basic dynamic load rating	C	41.5	kN
Basic static load rating	C ₀	26.5	kN
Fatigue load limit	P _u	1.1	kN
Reference speed		11000	r/min
Limiting speed		11000	r/min
Calculation factor	k _r	0.1	
Calculation factor	k _a	1.6	
Calculation factor	e	1.14	

Single bearing or bearing pair arranged in tandem

Calculation factor	X	0.35
Calculation factor	Y_0	0.26
Calculation factor	Y_2	0.57

Bearing pair arranged back-to-back or face-to-face

Calculation factor	X	0.57
Calculation factor	Y_0	0.52
Calculation factor	Y_1	0.55
Calculation factor	Y_2	0.93

Mass

Mass bearing	0.45	kg
--------------	------	----