


7309 BECBP


SKF Explorer

Dimensions



d		45	mm
D		100	mm
B		25	mm
d_1	$\approx$	66.5	mm
d_2	$\approx$	55.25	mm
D_1	$\approx$	79.9	mm
a		43	mm
$r_{1,2}$	min.	1.5	mm
$r_{3,4}$	min.	1	mm

Abutment dimensions



d_a	min.	54	mm
D_a	max.	91	mm
D_b	max.	94.4	mm
r_a	max.	1.5	mm
r_b	max.	1	mm

Calculation data

Basic dynamic load rating	C	61	kN
Basic static load rating	C_0	40.5	kN
Fatigue load limit	P_u	1.7	kN
Reference speed		9000	r/min
Limiting speed		9000	r/min
Calculation factor	k_r	0.1	
Calculation factor	k_a	1.6	
Calculation factor	e	1.14	

Single bearing or bearing pair arranged in tandem

Calculation factor	X	0.35
Calculation factor	Y_0	0.26
Calculation factor	Y_2	0.57

Bearing pair arranged back-to-back or face-to-face

Calculation factor	X	0.57
Calculation factor	Y_0	0.52
Calculation factor	Y_1	0.55
Calculation factor	Y_2	0.93

Mass

Mass bearing	0.82	kg
--------------	------	----