

# GEH 30 ES-2RS

Radial spherical plain bearing, requiring maintenance, sealed, metric sizes

These radial spherical plain bearings have a steel/steel sliding contact surface combination and a double-lip contact seal on both sides. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings. Compared to the GE series, they have a wider inner ring and a larger outside diameter, which enable higher load ratings and larger tilt angles.

- Designed for radial and combined radial and axial loads
- Long service life
- Minimal maintenance
- Suitable for heavy static, alternating or impact loads
- Enable larger tilt angles

## Overview

### Dimensions

|                   |       |
|-------------------|-------|
| Bore diameter     | 30 mm |
| Outside diameter  | 55 mm |
| Width, inner ring | 32 mm |
| Width, outer ring | 20 mm |

### Properties


|                                     |                        |
|-------------------------------------|------------------------|
| Maintenance                         | Relubrication required |
| Material, inner ring                | Bearing steel          |
| Material, outer ring                | Bearing steel          |
| Radial internal clearance           | CN                     |
| Relubrication feature               | With                   |
| Sealing                             | Seal on both sides     |
| Sealing type                        | Double-lip             |
| Sliding contact surface combination | Steel/steel, standard  |

### Performance

|                           |        |
|---------------------------|--------|
| Basic dynamic load rating | 80 kN  |
| Basic static load rating  | 400 kN |

# Technical Specification

|                                     |                        |
|-------------------------------------|------------------------|
| Maintenance                         | Relubrication required |
| Sliding contact surface combination | Steel/steel, standard  |
| Material, inner ring                | Bearing steel          |
| Material, outer ring                | Bearing steel          |
| Sealing                             | Seal on both sides     |
| Sealing type                        | Double-lip             |




## Dimensions

|          |             |                                                |
|----------|-------------|------------------------------------------------|
| d        | 30 mm       | Bore diameter                                  |
| D        | 55 mm       | Outside diameter                               |
| B        | 32 mm       | Width                                          |
| C        | 20 mm       | Width outer ring                               |
| $\alpha$ | 17 °        | Angle of tilt                                  |
| $d_k$    | 47 mm       | Raceway diameter inner ring                    |
| b        | 3.8 mm      | Width annular lubrication groove at outer ring |
| $b_1$    | 4 mm        | Width annular lubrication groove at inner ring |
| M        | 2.5 mm      | Diameter lubrication hole (outer ring)         |
| $r_1$    | min. 0.6 mm | Chamfer dimension bore                         |
| $r_2$    | min. 1 mm   | Chamfer dimension outer ring                   |

## Abutment dimensions

|       |              |                           |
|-------|--------------|---------------------------|
| $d_a$ | min. 33.7 mm | Abutment diameter shaft   |
| $d_a$ | max. 34.4 mm | Abutment diameter shaft   |
| $D_a$ | min. 48.5 mm | Abutment diameter housing |
| $D_a$ | max. 50.9 mm | Abutment diameter housing |
| $r_a$ | max. 0.6 mm  | Fillet radius shaft       |



$r_b$  max. 1 mm

Fillet radius housing

## Calculation data

|                              |       |          |
|------------------------------|-------|----------|
| Basic dynamic load rating    | C     | 80 kN    |
| Basic static load rating     | $C_0$ | 400 kN   |
| Specific dynamic load factor | K     | 100 N/mm |
| Specific static load factor  | $K_0$ | 500 N/mm |
| Material constant            | $K_M$ | 330      |

## Mass

|                    |         |
|--------------------|---------|
| Mass plain bearing | 0.35 kg |
|--------------------|---------|

# Terms and conditions

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

## Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app. Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service. Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

## Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

## Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

## Changes

SKF reserves the right to make changes or additions to this website / app at any time.